

Fujitsu LIFEBOOK S6420 Intel® Core™2 Duo T9400 33.8 cm (13.3") 2 GB DDR3-SDRAM 160 GB Intel® GMA X4500MHD Windows Vista Business

Brand : Fujitsu Product family: LIFEBOOK Product code:
VFY:S6420MF011DE 2700167

Product name: LIFEBOOK

S6420

13.3" TFT WXGA (1280x800), Intel Core 2 Duo T9400 2.53 GHz, 2GB DDR III, 160GB SATA HDD, DVD Super Multi, Intel GMA X4500MHD, 1.3MP webcam, UMTS, Windows Vista Home Edition / XP pro + Vodafone Testpacket

Fujitsu LIFEBOOK S6420. Processor family: Intel® Core™2 Duo, Processor: T9400, Processor frequency: 2.53 GHz. Display diagonal: 33.8 cm (13.3"), Display resolution: 1280 x 800 pixels. Internal memory: 2 GB, Internal memory type: DDR3-SDRAM. Total storage capacity: 160 GB, Optical drive: DVD Super Multi. Discrete graphics card model: Intel® GMA X4500MHD. Operating system installed: Windows Vista Business. Weight: 1.75 kg





	Processor special features	
33.8 cm (13.3")	Intel My WiFi Technology	×
'	Intel Anti-Theft Technology	×
16:10	Intel Hyper-Threading Technology	×
	Intel Turbo Boost Technology	×
Intel	Enhanced Intel SpeedStep	✓
Intel® Core™2 Duo	Technology	
T9400	Intel Clear Video HD Technology	×
2	Intel Clear Video Technology	×
2	Intel® InTru™ 3D Technology	×
2.53 GHz	Intel® Insider™	×
	Intel® Quick Sync Video Technology	×
	Intel Flex Memory Access	×
	•	×
		· •
	3,	
		X
		×
FSB	Intel Demand Based Switching	x
×	Intel Clear Video Technology for MID	×
EO	Intel 64	✓
35 W	Execute Disable Bit	✓
105 °C		×
410 M	Thermal Monitoring Technologies	×
107 mm²	Processor package size	35 x 35 mm
9.5	Processor code	SLGEK
×	Embedded options available	✓
	Intel Virtualization Technology for Directed I/O (VT-d)	×
	1280 x 800 pixels 16:10 Intel Intel® Core™2 Duo T9400 2 2 2.53 GHz 6 MB L2 Socket 479 1066 MHz 45 nm 64-bit Intel Core 2 Duo T9000 Series Penryn FSB x E0 35 W 105 °C 410 M 107 mm² 9.5	33.8 cm (13.3") 1280 x 800 pixels 16:10 Intel My WiFi Technology Intel Anti-Theft Technology Intel Hyper-Threading Technology Intel Turbo Boost Technology Intel SpeedStep Technology Intel Clear Video HD Technology Intel Clear Video Technology Intel® InTru™ 3D Technology Intel® InTru™ 3D Technology Intel® InSider™ Intel® Quick Sync Video Technology Intel® Intel® Quick Sync Video Technology Intel® Intel Elex Memory Access Intel Flex Memory Access Intel Trusted Execution Technology Intel Core 2 Duo T9000 Series Penryn FSB Intel Demand Based Switching Intel Clear Video Technology for MID Intel Enhanced Halt State Intel VT-x with Extended Page Tables (EPT) FSB Intel Demand Based Switching Intel Clear Video Technology for MID Intel 64 Execute Disable Bit Idle States Thermal Monitoring Technologies Processor package size Processor code Embedded options available Intel Virtualization Technology for

Memory		Processor special features	
Memory clock speed	1066 MHz	Intel Dual Display Capable Technology	×
Memory layout (slots x size)	2 x 1 GB	Intel FDI Technology	×
Memory, maximum *	4 GB	5.	
Storage		Intel Rapid Storage Technology	X
Total storage capacity *	160 GB	Intel Fast Memory Access Processor ARK ID	X 35562
Number of HDDs installed	1	Conflict-Free processor	X
Hard drive interface	SATA DVD Super Multi	·	^
Optical drive * Card reader integrated	DVD Super Multi	Battery	
	•	Number of battery cells	6
Graphics		Battery capacity	5200 mAh 5 h
Discrete graphics card model *	Intel® GMA X4500MHD	Battery life (max)	3 11
Discrete graphics card *		Power	
Maximum resolution	1920 x 1200 pixels	AC adapter power	80 W
Audio		AC adapter input voltage	100 - 240 V 4.22 A
Audio system	RealTek ALC262	AC adapter output current AC adapter output voltage	4.22 A 19 V
Number of built-in speakers	2	DC-in jack	√ ·
Camera			•
Front camera resolution (numeric)	1.3 MP	Security	
Network		Cable lock slot	✓
	Gigabit Ethernet, Wireless LAN,	Cable lock slot type	Kensington
Network interface	Bluetooth	Fingerprint reader	✓
Networking type	Gigabit Ethernet, Fast Ethernet, Ethernet	Password protection type	BIOS
Networking manufacturer	Marvel	Operational conditions	
Modem chip	MDC1.5	Operating temperature (T-T)	5 - 35 °C
Networking speed	10/100/1000 MBit/s	Operating relative humidity (H-H)	20 - 85%
Bluetooth	✓	Certificates	
			CE 00/236/EEC (EMC)
Bluetooth version	2.0+EDR		CE, 89/336/EEC (EMC),
Bluetooth version Ports & interfaces	2.0+EDR	Certification	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS,
Ports & interfaces		Certification	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi
	2.0+EDR 3 1		73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS,
Ports & interfaces USB 2.0 ports quantity *	3	Certification Weight & dimensions	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports	3	Weight & dimensions Width	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port	3 1 ×	Weight & dimensions Width Depth	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity	3 1 × 1	Weight & dimensions Width Depth Height	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports	3 1 X 1 1	Weight & dimensions Width Depth Height Height (front)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs	3 1 x 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight *	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type	3 1 X 1 1 1 1 X ✓ ✓ X 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1 Type II ✓ 1 x SIM	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included *	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports	3 1 X 1 1 1 1 X ✓ ✓ ✓ ✓ X 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out	3 1 X 1 1 1 1 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type	3 1 X 1 1 1 1 X ✓ ✓ ✓ ✓ X 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard	3 1 X 1 1 1 1 1 Type II ✓ 1 x SIM 1 ✓ S-Video	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke	3 1 X 1 1 1 1 1 Type II 1 x SIM 1 3 mm	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch	3 1 X 1 1 1 1 1 1 Type II 1 x SIM 1 y S-Video	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family Type	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device	3 1 X 1 1 1 1 1 1 Type II S-Video 3 mm 1.9 cm Touchpad	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family Type TV-in port	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device Keyboard number of keys	3 1 X 1 1 1 1 1 1 Type II 1 x SIM 1 y S-Video	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family Type TV-in port HDD user password	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device Keyboard number of keys Software	3 1 X 1 1 1 1 1 1 1 Type II I x SIM 1 S-Video 3 mm 1.9 cm Touchpad 85	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family Type TV-in port HDD user password Internal modem	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X V
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device Keyboard number of keys	3 1 X 1 1 1 1 1 1 Type II S-Video 3 mm 1.9 cm Touchpad	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless Infrared data port Graphics card family Type TV-in port HDD user password	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22.4 mm 2.24 cm 3.35 cm 1.75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X V

Processor special features

Intel Wireless Display (WiDi) Technology

×

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.