SAMSUNG

## Samsung ST ST96 Compact camera 14.6 MP CMOS 4320 x 3240 pixels Black

Brand : Samsung

Product code: EC-ST96ZZBPBE1

Product name : ST96

ST96 - 14.6MP, 4320 x 3240, CMOS, 2.7" TFT (320x240), 5x, TTL, F3.3-5.9, ±2EV (1/3EV),

Product family: ST

1920x1080/30fps, HDMI, USB 2.0, Black, 110g

Samsung ST ST96. Camera type: Compact camera, Megapixel: 14.6 MP, Sensor type: CMOS, Maximum image resolution: 4320 x 3240 pixels. Optical zoom: 5x, Digital zoom: 5x, Focal length range: 4.7 - 23.5 mm. Fastest camera shutter speed: 1/2000 s. HD type: Full HD, Maximum video resolution: 1920 x 1080 pixels. Display diagonal: 6.86 cm (2.7"). Internal memory: 16 MB. PictBridge. Weight: 110 g. Product color: Black





Picture quality		Display	
Camera type * Megapixel * Sensor type * Maximum image resolution *	Compact camera 14.6 MP CMOS 4320 x 3240 pixels	Display * Display diagonal * Display resolution Display resolution (numeric)	LCD 6.86 cm (2.7") 320 x 240 pixels 230000 pixels
Still image resolution(s) * Image stabilizer * Image formats supported *	1024 x 768,1920 x 1080,1984 x 1488,2592 x 1944,3648 x 2736,4320 x 2432,4320 x 2880,4320 x 3240 X IPG	Ports & interfaces PictBridge * USB version * DC-in jack	✓ 2.0 ✓
5 11	jrð	Camera	
Lens system Optical zoom * Digital zoom * Focal length range Minimum focal length (35mm film equiv) Maximum focal length (35mm film equiv) Minimum aperture number Maximum aperture number	5x 5x 4.7 - 23.5 mm 26 mm 130 mm 3.3 5.9	White balance * Scene modes * Shooting modes * Camera playback 3D Image editing Camera file system	Auto, Cloudy, Custom modes, Daylight, Fluorescent, Tungsten Panorama Auto, Movie, Program, Scene Movie, Single image, Slide show, Thumbnails ✓ Trimming DCF 2.0, DPOF 1.1, Exif 2.21
Focusing		Design Product color *	Black
Focus * Focus adjustment * Normal focusing range (tele) Normal focusing range (wide) Normal focusing range Macro focusing range (tele) Macro focusing range (wide)	TTL Auto 1.5 - ∞ 0.8 - ∞ 0.8 - 1.5 m 1 - 1.5 m 0.5 - 0.8 m	Battery Battery voltage Battery capacity Battery type Number of batteries supported Power requirements	3.7 V 740 mAh BP-70A 1 4.2V

Exposure		System requirements	
ISO sensitivity	100, 200, 400, 800, 1600, 3200	Mac compatibility	✓
Light exposure modes *	Auto	Operational conditions	
Light exposure control	Program AE	Operating temperature (T-T)	0 - 40 °C
Light metering *	Centre-weighted, Spot	Operating relative humidity (H-H)	5 - 85%
Shutter		Weight & dimensions	
Fastest camera shutter speed *	1/2000 s	Width	90 mm
Slowest camera shutter speed *	8 s	Depth	18.7 mm
Flash		Height	55 mm
Flash modes *	Auto, Fill-in, Flash off, Red-eye	Weight	110 g
Flash range (wide)	reduction, Slow synchronization 0.2 - 3.4 m	Packaging content	
Flash range (tele)	1 - 1.9 m	AC adapter included *	1
Flash recharging time	4 s	Batteries included	1
Flash exposure compensation	Image: A start of the start		
the second se		Other features	
Flash exposure correction	±2EV (1/2, 1/3 EV step)	Other features	110 MP
	±2EV (1/2, 1/3 EV step)	Other features Minimum storage drive space Minimum RAM	110 MB 512 MB
Flash exposure correction	±2EV (1/2, 1/3 EV step)	Minimum storage drive space	
Flash exposure correction Video		Minimum storage drive space Minimum RAM	512 MB
Flash exposure correction Video Video recording *	1	Minimum storage drive space Minimum RAM Minimum processor	512 MB Intel Core 2 Duo 1.66GHz
Flash exposure correction Video Video recording * Maximum video resolution *	✓ 1920 x 1080 pixels	Minimum storage drive space Minimum RAM Minimum processor Video capability	512 MB Intel Core 2 Duo 1.66GHz ✔
Flash exposure correction Video Video recording * Maximum video resolution * HD type *	✓ 1920 x 1080 pixels Full HD	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out	512 MB Intel Core 2 Duo 1.66GHz ✓ AV
Flash exposure correction Video Video recording * Maximum video resolution * HD type * Video resolutions Motion JPEG frame rate Analog signal format system	✓ 1920 x 1080 pixels Full HD 1280 x 720,1920 x 1080 pixels 30 fps	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out Interface	512 MB Intel Core 2 Duo 1.66GHz ✓ AV USB, HDMI USB CD-ROM GeForce 7600GT ATI
Flash exposure correction Video Video recording * Maximum video resolution * HD type * Video resolutions Motion JPEG frame rate Analog signal format system Audio	<ul> <li>1920 x 1080 pixels</li> <li>Full HD</li> <li>1280 x 720,1920 x 1080 pixels</li> <li>30 fps</li> <li>NTSC, PAL</li> </ul>	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out Interface Minimum system requirements	512 MB Intel Core 2 Duo 1.66GHz ✓ AV USB, HDMI USB CD-ROM GeForce 7600GT ATI X1600 DirectX 9.0c
Flash exposure correction Video Video recording * Maximum video resolution * HD type * Video resolutions Motion JPEG frame rate Analog signal format system	✓ 1920 x 1080 pixels Full HD 1280 x 720,1920 x 1080 pixels 30 fps	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out Interface Minimum system requirements Built-in flash	512 MB Intel Core 2 Duo 1.66GHz ✓ AV USB, HDMI USB CD-ROM GeForce 7600GT ATI X1600 DirectX 9.0c ✓
Flash exposure correction Video Video recording * Maximum video resolution * HD type * Video resolutions Motion JPEG frame rate Analog signal format system Audio	<ul> <li>1920 x 1080 pixels</li> <li>Full HD</li> <li>1280 x 720,1920 x 1080 pixels</li> <li>30 fps</li> <li>NTSC, PAL</li> </ul>	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out Interface Minimum system requirements Built-in flash Camera shutter speed	512 MB Intel Core 2 Duo 1.66GHz ✓ AV USB, HDMI USB CD-ROM GEForce 7600GT ATI X1600 DirectX 9.0c ✓ 8 - 1/2000 s
Flash exposure correction Video Video recording * Maximum video resolution * HD type * Video resolutions Motion JPEG frame rate Analog signal format system Audio Built-in microphone *	<ul> <li>1920 x 1080 pixels</li> <li>Full HD</li> <li>1280 x 720,1920 x 1080 pixels</li> <li>30 fps</li> <li>NTSC, PAL</li> </ul>	Minimum storage drive space Minimum RAM Minimum processor Video capability Video out Interface Minimum system requirements Built-in flash Camera shutter speed Compatible operating systems	512 MB Intel Core 2 Duo 1.66GHz ✓ AV USB, HDMI USB CD-ROM GeForce 7600GT ATI X1600 DirectX 9.0c ✓ 8 - 1/2000 s Windows XP/Vista/7 Mac OS 10.4



## 8806071587639

**Catalog Object Cloud** 



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.