Chieftec APS-450SB power supply unit 450 W 24-pin ATX ATX Silver

Brand : Chieftec

Product code: APS-450SB

Product name : APS-450SB

APS-450SB, 450W, 115-230V, 50 - 60Hz, ATX 12V 2.3

Chieftec APS-450SB power supply unit 450 W 24-pin ATX ATX Silver:

Equally cost-effective and future-oriented are the advantages of new A-135 series with fixed cables. In addition to the valuable 80 PLUS Bronze award, the 140 mm fan guarantees excellent cooling performance and allows a pleasantly quiet and stress-free working environment. Certainly it supports the newest generation of Intel processors with minimum load > 0.05A. Chieftec APS-450SB. Total power: 450 W, AC input voltage: 115 - 230 V, AC input frequency: 50 Hz.

Motherboard power connector: 24-pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Silver, Cooling type: Active, Fan diameter: 14 cm. Width: 150 mm, Depth: 87 mm, Height: 155 mm



Box

Non-Modular

80 PLUS Bronze

Power		Ports & interfaces	
Total power *	450 W	EPS power connector (8-pin)	×
AC input voltage *	115 - 230 V	CPU P4 connector (4-pin)	1
AC input frequency	50 Hz	Floppy drive power connector	1
Maximum input current (@110V)	+12V,+3.3V,+5V	Cabling type	Non-Modula
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	103 W		
Combined power (+5V)	103 W	80 PLUS certification *	80 PLUS Br
Max output current (+3.3V)	20 A	Purpose *	PC
Max output current (+12V1)	18 A	Power supply unit (PSU) form factor	ATX
Max output current (+12V2)	18 A	ATX version	2.3
Max output current (+5V)	20 A	Mean time between failures (MTBF)	2.5 100000 h
Max output current (-12V)	0,3 A		10000011
Max output current (+5Vsb)	2,5 A	Design	
Efficiency	85%	Product colour	Silver
Power protection features	Over current, Over voltage, Short circuit	Cooling type	Active
		Fan diameter	14 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	24-pin ATX	On/off switch	✓
Number of SATA power connectors	4	Weight & dimensions	
Peripheral (Molex) power connectors (4-pin) *	3	Width	150 mm
		Depth	87 mm
		Height	155 mm
		licigite	133 1111

Publication date: 16-JUL-2025. Prints or copies of Information are only valid on the printed Publication date

Packaging data Package type

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.