

Fujitsu LIFEBOOK S6420 Intel® Core™2 Duo T9400 33,8 cm (13.3") 2 GB DDR3-SDRAM 160 GB Intel® GMA X4500MHD Windows Vista Business

Brand : Fujitsu Product family: LIFEBOOK Product code:
VFY:S6420MF011DE 2700167

Product name: LIFEBOOK

S6420

13.3" TFT WXGA (1280x800), Intel Core 2 Duo T9400 2.53 GHz, 2GB DDR III, 160GB SATA HDD, DVD Super Multi, Intel GMA X4500MHD, 1.3MP webcam, UMTS, Windows Vista Home Edition / XP pro + Vodafone Testpacket

Fujitsu LIFEBOOK S6420. Processor type: Intel® Core™2 Duo, Processor: T9400, Processor frequency: 2,53 GHz. Display diagonal: 33,8 cm (13.3"), Display resolution: 1280 x 800 pixels. Internal memory: 2 GB, Internal memory type: DDR3-SDRAM. Total storage capacity: 160 GB, Optical drives: DVD Super Multi. Discrete graphics card model: Intel® GMA X4500MHD. Operating system software: Windows Vista Business. Weight: 1,75 kg





Display		Processor special features	
Display diagonal *	33,8 cm (13.3")	Intel My WiFi Technology	x
Display resolution *	1280 x 800 pixels	Intel Anti-Theft Technology	×
Native aspect ratio	16:10	Intel Hyper-Threading Technology	×
Processor		Intel Turbo Boost Technology	×
Processor manufacturer *	Intel	Enhanced Intel SpeedStep	✓
Processor type *	Intel® Core™2 Duo	Technology	•
Processor *	T9400	Intel Clear Video HD Technology	×
Processor number of cores	2	Intel Clear Video Technology	×
Processor threads	2	Intel® InTru™ 3D Technology	×
Processor frequency *	2,53 GHz	Intel® Insider™	×
Processor cache	6 MB	Intel® Quick Sync Video Technology	×
Processor cache type Processor socket	L2 Socket 479	Intel Flex Memory Access	×
Processor system bus	1066 MHz	Intel AES New Instructions	×
Processor lithography	45 nm	Intel Trusted Execution Technology	✓
Processor operating modes	64-bit	Intel Enhanced Halt State	X
Processor series	Intel Core 2 Duo T9000 Series	Intel VT-x with Extended Page	^
Processor codename	Penryn	Tables (EPT)	×
Bus type	FSB	Intel Demand Based Switching	×
FSB Parity	×	Intel Clear Video Technology for MID	×
Stepping	E0	Intel 64	✓
Thermal Design Power (TDP)	35 W	Execute Disable Bit	✓
Tjunction	105 °C	Idle States	×
Number of Processing Die Transistors	410 M	Thermal Monitoring Technologies	×
Processing die size	107 mm²	Processor package size	35 x 35 mm
CPU multiplier (bus/core ratio)	9,5	Processor code	SLGEK
ECC supported by processor	×	Embedded options available	✓
Memory		Intel Virtualization Technology for Directed I/O (VT-d)	×
Internal memory * Internal memory type	2 GB DDR3-SDRAM	Intel Virtualization Technology (VT- \mathbf{x})	•

Memory		Processor special features	
Memory speed	1066 MHz	Intel Dual Display Capable	×
Memory layout (slots x size)	2 x 1 GB	Technology	
Maximum memory *	4 GB	Intel FDI Technology	X
Storage		Intel Rapid Storage Technology	×
Total storage capacity *	160 GB	Intel Fast Memory Access	×
Number of HDDs installed	1	Processor ARK ID	35562
Hard drive interface	SATA	Conflict-Free processor	×
Optical drives *	DVD Super Multi	Battery	
Card reader integrated	1	Number of battery cells	6
Graphics		Battery capacity	5200 mAh
Discrete graphics card model *	Intel® GMA X4500MHD	Battery life (max)	5 h
Discrete graphics card *	✓	Power	
Maximum resolution	1920 x 1200 pixels	AC adapter power	80 W
Audio		AC adapter input voltage	100 - 240 V
Audio system	RealTek ALC262	AC adapter output current	4,22 A
Number of built-in speakers	2	AC adapter output voltage	19 V
	-	DC-in jack	✓
Camera	4.2.440	Security	
Front camera resolution (numeric)	1,3 MP	Cable lock slot	✓
Network		Cable lock slot type	Kensington
Network interface	Gigabit Ethernet, Wireless LAN,	Fingerprint reader	✓
	Bluetooth	Password protection type	BIOS
Networking type	Gigabit Ethernet, Fast Ethernet, Ethernet	. 21	2.00
Networking manufacturer	Marvel	Operational conditions	5 25 20
Modem chip	MDC1.5	Operating temperature (T-T)	5 - 35 °C
Networking speed	10/100/1000 MBit/s	Operating relative humidity (H-H)	20 - 85%
Bluetooth	✓	Certificates	
Bluetooth version	2.0+EDR		CE, 89/336/EEC (EMC),
Didetootii versioii	Z.UTLDR		
Ports & interfaces	Z.UTLUN	Certification	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS,
Ports & interfaces	3	Certification	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi
			73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS,
Ports & interfaces USB 2.0 ports quantity *	3	Certification Weight & dimensions	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports	3		73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port	3 1 ×	Weight & dimensions Width Depth	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity	3 1 × 1	Weight & dimensions Width Depth Height	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports	3 1 X 1 1	Weight & dimensions Width Depth Height Height (front)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs	3 1 x 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight *	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in	3 1 X 1 1 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector	3 1 X 1 1 1 1 V V V V	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot	3 1 X 1 1 1 1 X ✓	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type	3 1 X 1 1 1 1 X ✓ ✓ X 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max)	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports	3 1 X 1 1 1 1 X ✓ ✓ ✓ X 1 Type II ✓ 1 x SIM	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included *	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports	3 1 X 1 1 1 1 X ✓ ✓ ✓ ✓ X 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out	3 1 X 1 1 1 1 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type	3 1 X 1 1 1 1 1 Type II ✓ 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard	3 1 X 1 1 1 1 1 Type II ✓ 1 x SIM 1 ✓ S-Video	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family Type	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke	3 1 X 1 1 1 1 1 Type II 1 x SIM 1	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch	3 1 X 1 1 1 1 1 1 Type II 1 x SIM 1 y S-Video	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family Type	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, RoHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device	3 1 X 1 1 1 1 1 1 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family Type TV-in port	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device Keyboard number of keys Software	3 1 X 1 1 1 1 1 1 1 Type II	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family Type TV-in port HDD user password Internal modem Modem speed	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X 56 Kbit/s
Ports & interfaces USB 2.0 ports quantity * Ethernet LAN (RJ-45) ports DVI port VGA (D-Sub) ports quantity Firewire (IEEE 1394) ports Headphone outputs S/PDIF out port Microphone in Line-in Docking connector ExpressCard slot CardBus PCMCIA slots quantity CardBus PCMCIA slot type SmartCard slot I/O ports Modem (RJ-11) ports TV-out TV-out type Keyboard Keyboard keystroke Keyboard key pitch Pointing device Keyboard number of keys	3 1 X 1 1 1 1 1 1 1 1 X ✓ ✓ ✓ ✓ S-Video 3 mm 1,9 cm Touchpad 85	Weight & dimensions Width Depth Height Height (front) Height (rear) Weight * Video Video adapter features External video modes refresh rate (max) Packaging content AC adapter included * Other features BIOS flash ROM Wireless technologies Infrared data port Graphics card family Type TV-in port HDD user password Internal modem	73/23/EEC,99/5/EEC (R&TTE),CE!, R&TTE, FCC, GS, UL/cUL, CB, ROHS, WHQL, TBR21, Energy Star, WiFi certified 314 mm 234 mm 22,4 mm 2,24 cm 3,35 cm 1,75 kg DirectX 10, DualView 60 Hz Phoenix TrustedCore IEEE 802.11a/g/n Intel PC X V

Processor special features

Intel Wireless Display (WiDi) Technology

×

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.