


ASUS P8H67-M LX Rev.3.0 LGA 1155 (Socket H2) micro ATX

Brand : ASUS

Article code: 90-MIBEQB-G0UBY0GZ

Product name : P8H67-M LX Rev.3.0



P8H67-M LX LGA1155, Intel H67, DDR 1333/1066MHz, PCIe2.0 x16, 4 xSATA 3.0Gb/s, 2 xSATA 6.0Gb/s, uATX
 ASUS P8H67-M LX Rev.3.0. Processor manufacturer: Intel, Processor socket: LGA 1155 (Socket H2), Compatible processor series: Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7. Maximum internal memory: 16 GB, Memory channels: Dual-channel, ECC compatibility: Non-ECC. RAID levels: 0, 1, 5, 10. Maximum graphics card memory: 1748 MB, Graphics card family: Intel. Ethernet interface type: Gigabit Ethernet, LAN controller: Realtek RTL8112L

Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 2.0 ports quantity *	6
Processor socket *	LGA 1155 (Socket H2)	Ethernet LAN (RJ-45) ports *	1
Compatible processor series *	Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7	PS/2 ports quantity	1
System bus rate	5 GT/s	VGA (D-Sub) ports quantity *	1
Memory		DVI-D ports quantity *	1
Number of memory slots *	2	Headphone outputs	3
Memory channels	Dual-channel	Network	
ECC compatibility	Non-ECC	Ethernet interface type	Gigabit Ethernet
Supported memory clock speeds	1066,1333 MHz	LAN controller	Realtek RTL8112L
Maximum internal memory *	16 GB	Features	
Storage controllers		Audio chip	Realtek ALC887
RAID levels	0, 1, 5, 10	Audio output channels *	7.1 channels
Graphics		Component for *	PC
Maximum graphics card memory	1748 MB	Motherboard form factor *	micro ATX
Parallel processing technology support *	Not supported	Power source type	ATX
On-board graphics card	✓	Expansion slots	
Graphics card family	Intel	PCI Express x4 slots	1
Internal I/O		PCI Express x16 slots	1
USB 2.0 connectors *	4	PCI slots	2
Number of SATA connectors	6	BIOS	
Front panel audio connector	✓	BIOS type *	AMI
ATX Power connector (24-pin)	✓	BIOS memory size	32 Mbit
Number of EATX power connectors	1	ACPI version	2.0a
CPU fan connector	✓	Weight & dimensions	
Chassis intrusion connector	✓	Width	9.61" (244 mm)
		Depth	8.39" (213 mm)

Internal I/O		Packaging content	
Number of COM connectors	1	Drivers included	✓
		Other features	
		Quick installation guide	✓

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.